

Price list

January 2021



WEINZIERL ENGINEERING GmbH
Achatz 3-4
84508 Burgkirchen an der Alz
GERMANY

Tel.: +49 8677 / 916 36 – 0
E-Mail: info@weinzierl.de
Web: www.weinzierl.de

Content

1	Basic devices for KNX	3
2	KNX Compact IO	5
3	KNX Multi IO and extensions	7
4	KNX IP	9
5	KNX BAOS	11
6	KNX Gateways	12
7	MATCH 55 push button series	13
8	KNX RF	15
9	KNX EnOcean Gateways	16

History / Change log

Description	Date	Author
Creation 2021	2021-01-21	Ma
Updated links	2021-01-28	Ma

1 Basic devices for KNX

KNX USB Interface 312 – KNX USB interface



Compact USB data interface between a PC or laptop and the KNX bus. The device can be used as a programming interface for the ETS® software.

- Support of KNX Long Frames
- Support of Weinzierl BAOS Protocol V2
- Status display via 2 LEDs
- Connections: KNX, USB type B
- For DIN rail, width 1 unit (18 mm)

[KNX USB Interface 312](#)

Art. no. 5229

Gross price

178.00 €

KNX USB Interface Stick 332 – KNX USB interface



Compact USB data interface in stick format between a PC or laptop and the KNX bus. The stick can be used as a programming interface for the ETS® software.

- Support of KNX Long Frames
- Support of Weinzierl BAOS Protocol V2
- Status display via 2 LEDs
- Connections: KNX, USB type A
- Dimensions (LxWxH): 58 x 18 x 12 mm
- Delivery in plastic box

[KNX USB Interface Stick 332](#)

Art. no. 5254

Gross price

178.00 €

KNX PowerSupply 365 – KNX power supply 640 mA



Bus power supply with high efficiency and low space requirement. Integrated bus choke and additional output for auxiliary voltage.

- Output current 640 mA with bus choke
- Status display via 3 LEDs
- Connections: KNX, auxiliary voltage output 29 V_{DC}, plugable screw terminal for 230 V_{AC}
- For DIN rail, width 4 units (72 mm)

[KNX PowerSupply 365](#)

Art. no. 5335

Gross price

228.00 €

KNX PowerSupply DGS 366 – KNX power supply 640 mA with diagnostic



Bus power supply with high efficiency and low space requirements. Comprehensive diagnostic functions. Integrated bus choke and additional output for auxiliary voltage.

- Output current 640 mA with bus choke
- Graphic display (OLED)
- Integrated KNX node with diagnostic and logic functions
- Connections: KNX, auxiliary voltage output 29 V_{DC}, plugable screw terminal for 230 V_{AC}
- For DIN rail, width 4 units (72 mm)

[KNX PowerSupply DGS 366](#)

Art. no. 5207

Gross price

328.00 €

KNX PowerSupply USB 367 – KNX power supply 640 mA with USB



Bus power supply like model KNX PowerSupply DGS 366, but with additional integrated USB interface.

- Programming interface for ETS®
- Support of KNX Long Frames
- USB connector: Type Micro B

[KNX PowerSupply USB 367](#)

Art. no. 5219

Gross price

378.00 €

KNX LineCoupler 650 – KNX line coupler



KNX TP line coupler in compact design. It connects two KNX segments (e.g. a KNX line with a KNX area).

- Status display via 3 LEDs
- Extended filter table for main group 0..31
- Galvanic isolation of the lines
- Buffer for 2x50 telegrams
- Support of KNX Long Frames
- Connections: KNX main line, KNX subline
- For DIN rail, width 1 unit (18 mm)

[KNX LineCoupler 650](#)

Art. no. 5233

Gross price

248.00 €

KNX IP LineMaster 762 → see page 10

KNX RF/TP Coupler 673 *secure* → see page 15

2 KNX Compact IO

KNX IO 410 – KNX binary input 4-fold for 12..230 V \sim

KNX IO 411 – KNX binary input 4-fold for potential free contacts



Compact binary input with 4 channels for controlling lights, shutters, etc.

- Switching, dimming, shutters, scenes, pulse counter
- Integrated logic and timer functions
- Galvanically isolated
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 410](#): for 12..230 V \sim

[KNX IO 411](#): for potential free contacts

Art. no. 5230

Gross price

98.00 €

Art. no. 5231

Gross price

98.00 €

KNX IO 510 – KNX switch actuator 2-fold



Compact switching actuator with 2 outputs. Functions for universal output, staircase lighting, heating actuator, etc.

- 2 output relays 230 V \sim , 8 A, bistable
- Switching, staircase function, heating actuator
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 510](#)

Art. no. 5224

Gross price

98.00 €

KNX IO 511 – KNX switch actuator 1-fold and binary input 2-fold



Compact switch actuator with one bistable output and 2 binary inputs. Suitable as KNX compatible replacement for conventional impulse switches (output: light, input 1: pushbutton, input 2: L for zero-crossing detection).

- 1 output relay 230 V \sim , 16 A, bistable
- Switching, staircase function, heating actuator
- 2 inputs 12..230 V \sim , galvanically isolated
- Switching, dimming, shutters, scenes, pulse counter
- Zero-crossing detection via input channel
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)


[KNX IO 511](#)

Art. no. 5232

Gross price

98.00 €

KNX IO 520 – KNX blind actuator 1-fold and binary input 2-fold



Compact blind/shutter actuator with two additional binary inputs. Numerous functions including position drive via time calculation.

- 1 shutter output, 230 V \sim , 8 A
- Drive directions electro-mechanically locked against each other
- For blinds, shutters or window drives
- Approach position via time calculation
- 2 inputs 12..230 V \sim , galvanically isolated
- Switching, dimming, shutters, scenes, pulse counter
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 520](#)

Art. no. 5225

Gross price

98.00 €

KNX IO 530 – KNX universal dimming actuator 1-fold and binary input 2-fold



Compact 230 V universal dimmer with one output and 2 binary inputs. The dimmer supports numerous functions (staircase function, snooze function), as well as phase angle or phase cut-off control.

- Compatible with incandescent lamps, as well as LED retrofit
- Dimmer output for 230 V~ / 200 W
- Scenes, sequencer, staircase function, adjustable dimming curve
- 2 binary inputs for 230 V~ same potential as dimming actuator
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 530](#)

Art. no. 5312

Gross price

128.00 €

KNX IO 532 – KNX LED dimming actuator 1-fold and switching actuator 1-fold



Compact dimming actuator with one PWM output for dimming LEDs and one relay output. The dimming actuator can be used e.g. for LED panels/strips. The relay output can be used to switch the LED power supply.

- Output for 12-24 V= / 6 A, PWM dimmer
- Scenes, sequencer, staircase function, adjustable dimming curve
- Relay 230 V~ / 8 A, bistable
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 532](#)

Art. no. 5313

Gross price

128.00 €

KNX IO 534 CV – KNX LED dimming actuator 4-fold with constant voltage

KNX IO 536 CC – KNX LED dimming actuator 4-fold with constant current



Compact 4-fold dimming actuator with RGB, RGBW and Tunable White (TW) functions. The dimming actuator can be used e.g. for LED panels/strips with RGB / RGBW / Tunable White or for 4 independent dimming channels.

- Output for 12-24 V= / 6 A, freely distributable (for CV), PWM dimmer
- Scenes, sequencer, staircase function, adjustable dimming curve
- Integrated logic and timer functions
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 534 CV](#): Constant voltage

[KNX IO 536 CC](#): Constant current (available from Q2/2021)

Art. no. 5314

Gross price

148.00 €

Art. no. 5354

Gross price

148.00 €

KNX IO 546 – KNX 1..10 V dimming actuator 1-fold and switching actuator 1-fold



Compact dimming/switching actuator with one dimming channel for the connection of active electronic ballasts (ECG) with a 0/1..10 V= interface and one relay output. The relay output can be used for switching the load.

- Output for 0/1..10 V= / max. 50 mA
- Scenes, sequencer, staircase function, adjustable dimming curve
- Relay 230 V~ / 8 A, bistable
- Integrated logic and timer functions
- Also compatible with 0..10 V= actuators (valves)
- Connections: KNX, plugable screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[KNX IO 546](#)

Art. no. 5315

Gross price

108.00 €

3 KNX Multi IO and extensions

KNX Multi IO 570 – KNX input and output module 48-fold

Universal input and output module for building control. The device offers 48 digital channels. Each channel can be used as a binary input, binary output or shutter output. Input channels can be used to connect push buttons. Output channels can directly control signal LEDs, external coupling relays or shutter relays. The peripheral devices (e.g. relays) are supplied by an external power supply (24 V=).



- Flexible configuration of the channels as binary inputs, outputs or shutter outputs
- OLED display and buttons for manual operation
- Integrated USB interface for programming with ETS®
- Support of KNX Long Frames
- Output current max. 100 mA per channel
- Connections: KNX, USB Micro Type B, plugable screw terminals for 24 V= (input), plugable screw terminals for IO
- For DIN rail, width 4 units (72 mm)

[KNX Multi IO 570](#)

Art. no. 5267

Gross price

398.00 €

KNX IP Multi IO 580 – KNX input and output module 48-fold for IP

Universal input and output module for building control for KNX IP. The device works with the medium KNX IP and is connected to the KNX installation via LAN/Ethernet. The device provides 48 digital channels. Each channel can be used as binary input, binary output or shutter output. Input channels can be used to connect push buttons. Output channels can directly control signal LEDs, external coupling relays or shutter relays. The peripheral devices (e.g. relays) are supplied by an external power supply (24 V=).



- Flexible configuration of the channels as binary inputs, outputs or shutter outputs
- OLED display and buttons for manual operation
- Output current max. 100 mA per channel
- Connections: LAN RJ-45 (KNX IP), plugable screw terminals for 24 V= (input), plugable screw terminals for IO
- For DIN rail, width 6 units (108 mm)

[KNX Multi IO 580](#)

Art. no. 5238

Gross price

490.00 €

Multi IO Extension Switch 590 – Coupling relay for Multi IO (for operation with art. no. 5267, 5238)

The relay extension serves as a power-saving alternative for commercially available coupling relays for operation with art. no. 5267, 5238. Bistable relay internal, external control like monostable relay.



- Reduction of the holding current by up to 95 %
- Input (signal) 24 V= / Output 230 V~ / 10 A
- Pluggable relay 250 V~ / 16 A, bistable
- Integrated fuse (5 x 20 mm) to protect high-value devices
- Connections: Screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[Multi IO Extension Switch 590](#)

Art. no. 5321

Gross price

38.00 €

Replacement and spare relays – Coupling relays for Multi IO



Spare relay for Multi IO Extension Switch 590 with art. no. 5321.

[Spare relay](#): Standard

10 pcs

Art. no. 5347

Gross price

49.80 €

[Spare relay](#): with tungsten precontact

10 pcs

Art. no. 5348

Gross price

74.40 €

[Spare relay](#): with manual operation

10 pcs

Art. no. 5349

Gross price

69.80 €

Multi IO Extension Shutter 592 – Shutter relay for Multi IO (for operation with art. no. 5267, 5238)



Double relay especially for the control of blinds and shutters. The double relay is connected to only one output of a KNX Multi IO. Directional control of the relay outputs is achieved by coding the input voltage.
For operation with art. no. 5267, 5238.

- Direction control by the output signal of the KNX Multi IO
- Outputs electro-mechanically locked against each other
- Input (signal) 24 V⁻ / Output 230 V[~] / 6 A
- Pluggable relay 250 V[~] / 6 A
- Integrated fuse (5 x 20 mm) to protect high-value devices
- Connections: Screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

[Multi IO Extension Shutter 592](#)

Art. no. 5322

Gross price

48.00 €

Replacement and spare relays – Shutter relay for Multi IO



Spare relay for Multi IO Extension Shutter 592 with art. no. 5322.

[Spare relay](#): Standard

10 pcs

Art. no. 5346

Gross price

42.80 €

Standard coupling relay – Coupling relay for Multi IO



Standard coupling relay for operation with art. no. 5267, 5238.

- Extension of the KNX multi series, switching function
- Input (signal) 24 V⁻ / Output 230 V[~] / 10 A
- Relay 250 V[~] / 16 A, monostable
- Connections: Screw terminals for IO
- For DIN rail, width 1 unit (18 mm)

Standard coupling relay

10 pcs

Art. no. 5350

Gross price

118.90 €

Replacement and spare relays – Coupling relays for Multi IO



Spare relay for standard coupling relay with art. no. 5350.

Spare relay: Standard

10 pcs

Art. no. 5351

Gross price

42.80 €

4 KNX IP

KNX IP Interface 731 – KNX IP interface

Compact programming interface for connecting one or more PCs to the KNX bus (e.g. for the ETS®). Connection is made via a LAN interface (IP). Power is supplied via the KNX bus.

Note: The device is available until further notice.

For new installations KNX IP Interface 732 secure is recommended.



- KNXnet/IP tunneling, 5 tunnel connections
- Support of KNX Long Frames
- Status display via 3 LEDs
- Power supply via KNX bus
- Connections: KNX, LAN RJ-45
- For DIN rail, width 1 unit (18 mm)

[KNX IP Interface 731](#)

Art. no. 5242

Gross price

199.00 €

KNX IP Interface 732 secure – KNX IP interface

Compact programming interface for connecting one or more PCs to the KNX bus (e.g. for ETS®). Support of KNX IP Security. Connection is made via a LAN interface (IP). Power is supplied via the KNX bus.

- KNXnet/IP tunneling, 8 tunnel connections
- Support of KNX Security
- Support of KNX Long Frames
- Status display via 3 LEDs
- Power supply via KNX bus
- Connections: KNX, LAN RJ-45
- For DIN rail, width 1 unit (18 mm)

[KNX IP Interface 732 secure](#)

Art. no. 5248

Gross price

199.00 €

KNX IP Router 751 – KNX IP router

Compact IP router for forwarding telegrams between different lines via a LAN (IP) as a fast backbone. The device also serves as a programming interface between one or more PCs and the KNX bus (e.g. for the ETS®).

Note: The device is available until further notice.

For new installations KNX IP Router 752 secure is recommended.



- KNXnet/IP routing
- KNXnet/IP tunneling, 5 tunnel connections
- Support of KNX Long Frames
- Extended filter table for main group 0..31
- Buffer for 150 telegrams
- Status display via 3 LEDs
- Power supply via KNX bus
- Connections: KNX, LAN RJ-45
- For DIN rail, width 1 unit (18 mm)

[KNX IP Router 751](#)

Art. no. 5243

Gross price

348.00 €

KNX IP Router 752 secure – KNX IP router

Compact IP router for forwarding telegrams between different lines via a LAN (IP) as a fast backbone. Support of KNX IP Security. The device also serves as a programming interface between one or more PCs and the KNX bus (e.g. for the ETS®).

- KNXnet/IP routing
- KNXnet/IP tunneling, 8 tunnel connections
- Support of KNX Security
- Support of KNX Long Frames
- Extended filter table for main group 0..31
- Buffer for 150 telegrams
- Status display via 3 LEDs
- Power supply via KNX bus
- Connections: KNX, LAN RJ-45
- For DIN rail, width 1 unit (18 mm)

[KNX IP Router 752 secure](#)

Art. no. 5249

Gross price

348.00 €

KNX IP LineMaster 762 – KNX power supply 640 mA with IP router

The device combines the central functions of a KNX bus line: Bus power supply with bus choke, KNX IP router and KNX IP interface with low space requirement. Comprehensive diagnostic functions. The KNX IP router in the LineMaster enables the forwarding of telegrams between different lines via a LAN (IP) as a fast backbone. The device also serves as a programming interface between a PC and the KNX bus (e.g. for the ETS®).



- Output current 640 mA with bus choke
- KNXnet/IP routing
- KNXnet/IP tunneling, 6 tunnel connections
- Support of KNX Long Frames
- Graphic display (OLED)
- Extended filter table for main group 0..31
- Buffer for 150 telegrams
- Connections: KNX, auxiliary voltage 29 V~, LAN RJ-45, plugable screw terminals for 230 V~.
- For DIN rail, width 6 units (108 mm)

[KNX IP LineMaster 762](#)

Art. no. 5212

Gross price

518.00 €

5 KNX BAOS

KNX IP BAOS 773 – KNX IP interface with object server, 250 data points

KNX IP BAOS 774 – KNX IP interface with object server, 1000 data points



KNX IP interface to the KNX bus, both on telegram level (KNXnet/IP tunneling) and on data point level (KNX application layer). Thus clients can access the group objects directly via TCP/IP or UDP/IP using a binary protocol. Java Script Object Notation (JSON) is available as an alternative protocol for use in web browsers.

- BAOS binary V2 & JSON web services
- KNXnet/IP tunneling, 5 tunnel connections
- 10 BAOS connections
- Status displays via 3 LEDs
- Power supply via KNX bus
- Connections: KNX, LAN RJ-45
- For DIN rail, width 1 unit (18 mm)

[KNX IP BAOS 773](#): 250 data points

Art. no. 5262

Gross price

288.00 €

[KNX IP BAOS 774](#): 1000 data points

Art. no. 5263

Gross price

348.00 €

KNX IP BAOS 777 – KNX IP universal interface with web server and visualization



Universal KNX IP interface with integrated web server and visualization. Convenient operation of the building installation via the web browser of a PC or mobile device.

- Integrated web server with visualization
- Configuration of the visualization with ETS
- E-Mail, NTP, timer and history function
- BAOS protocol incl. RESTful API
- Power over Ethernet (PoE)
- KNXnet/IP tunneling, 8 tunnel connections
- 10 BAOS connections
- Graphic display (OLED)
- Connections: KNX, LAN RJ-45, 12-30 V=
- For DIN rail, width 2 units (36 mm)

[KNX IP BAOS 777](#)

Art. no. 5193

Gross price

448.00 €

KNX Serial 870 – Serial interface to KNX



Serial interface to the KNX bus with RS-232.

- Telegram format FT1.2 (PEI 10, EMI2)
- Object server with 250 data points
- BAOS binary V1
- Galvanically isolated
- Connections: KNX, RS232 (Sub-D, fem.)
- For DIN rail, width 1 unit (18 mm)

[KNX Serial 870](#)

Art. no. 5122

Gross price

190.00 €

KNX BAOS Module 838 kBerry – Extension module for Raspberry Pi



KNX module with serial protocol as expansion card for Raspberry Pi.

- 1000 data points
- Dimensions (LxW): 56 x 35 mm
- Free [BAOS SDK](#) for Raspian

[KNX BAOS Module 838 kBerry](#)

Art. no. 5208

Gross price

68.00 €

6 KNX Gateways

KNX DMX Gateway 544 – KNX gateway to DMX512



Compact gateway between KNX and DMX512 with up to 64 freely configurable channels. Master mode (KNX to DMX luminaires) and slave mode (DMX control to KNX actuators).

- Assignment between KNX and DMX512 via ETS® parameters
- Master: up to 64 individual dimming channels or up to 8 RGB/RGBW channels
- Slave: up to 64 DMX addresses evaluated individually
- 4 sequencers for complex time sequences
- Status display via 3 LEDs
- Connections: KNX, plugable screw terminals for DMX512, power supply
- For DIN rail, width 1 unit (18 mm)

[KNX DMX Gateway 544](#)

Art. no. 5358

Gross price

298.00 €

KNX Modbus RTU Gateway 886 – KNX gateway to modbus RTU



Compact KNX / modbus gateway with 250 freely configurable channels (KNX data points). The device allows easy integration of modbus devices supporting the RTU protocol via RS-485 into KNX installations. It can be used as modbus master or slave. The assignment between KNX objects and modbus registers is done via parameters in the ETS® - no further tool is required.

- Modbus master or slave mode
- Assignment between KNX and modbus via ETS® parameters
- 250 data points
- Status display via 3 LEDs
- Connections: KNX, plugable screw terminals for modbus, power supply
- For DIN rail, width 1 unit (18 mm)

[KNX Modbus RTU Gateway 886](#)

Art. no. 5256

Gross price

348.00 €

7 MATCH 55 push button series

KNX TP Push Button 420 *secure* with single rocker – KNX push button MATCH 55 series

KNX TP Push Button 420 *secure* with double rocker – KNX push button MATCH 55 series

KNX push button of the MATCH 55 series, with integrated bus coupling unit. The push button insert fits numerous switch ranges available on the market with 55 mm internal dimensions. Smooth and quiet push button operation. Optional support of KNX Security.



- Pleasantly soft and quiet pressure point
- Support of KNX Data Security
- Powerful KNX application for switching, dimming and shutters
- Functions for scenes, sequences and RGB control
- Mounting kit included (without design frame)
- Connections: KNX
- Rockers for standard frames with internal dimensions 55 x 55 mm
- Dimensions wall mounting plate: 71 x 71 mm, for flush mounted box 68 mm

[KNX TP Push Button 420 *secure*](#): Single rocker

Art. no. 5375

Gross price

78.00 €

[KNX TP Push Button 420 *secure*](#): Double rocker

Art. no. 5325

Gross price

83.00 €

KNX TP Push Button Interface 420 *secure* – KNX push button interface 4-fold



Push button interface for the KNX bus for the connection of up to four conventional push buttons or potential free contacts. In addition, the device offers two outputs for LEDs. Optional support of KNX Security.

- Support of KNX Data Security
- Powerful KNX application for switching, dimming and shutters
- Functions for scenes, sequences and RGB control
- Including pluggable connection cable 150 mm
- Connections: KNX, 4-channel binary input, 2 ext. LEDs
- Dimensions without bus terminal (LxWxH): 40 x 40 x 11 mm

[KNX TP Push Button Interface 420 *secure*](#)

Art. no. 5385

Gross price

75.00 €

24V Push Button 436 with single rocker – Potential free push button MATCH 55 series

24V Push Button 436 with double rocker – Potential free push button MATCH 55 series



Push button for extra low voltage of the MATCH 55 series, for direct connection to push button inputs of, for example, smart home control centers, PLC controls or push button interfaces of any bus systems. The optional terminal block enables the screwless connection of cables with a cross section of up to 0.75 mm².

- Pleasantly soft and quiet pressure point
- Mounting kit included (without design frame)
- Connections: pluggable connection cable 150 mm
- Rockers for standard frames with internal dimensions 55 x 55 mm
- Dimensions wall mounting plate: 71 x 71 mm, for flush mounted box 68 mm

[24V Push Button 436](#): Single rocker

Art. no. 5409

Gross price

47.00 €

[24V Push Button 436](#): Double rocker

Art. no. 5410

Gross price

49.00 €

[Terminal block for 436](#)

Art. no. 5413

Gross price

22.00 €

KNX RF / ENO Push Button 440 *secure* with single rocker – KNX push button MATCH 55 series

KNX RF / ENO Push Button 440 *secure* with double rocker – KNX push button MATCH 55 series

KNX wireless push button of the MATCH 55 series, with integrated bus coupling unit. The wireless push button offers support for EnOcean and KNX RF in one device. The device works in EnOcean mode without configuration (EnOcean Security is activated by a simple push button combination). By configuration with ETS® the push button switches to KNX RF mode and offers optional support of KNX Security.



- Pleasantly soft and quiet pressure point
- EnOcean 868.3 MHz, ASK, EEP F6-02-01 / -03
- Support of EnOcean Security
- KNX RF 868.3 MHz, FSK, S-Mode
- Support of KNX Data Security
- Powerful KNX application for switching, dimming and shutters
- Functions for scenes, sequences and RGB control
- Integrated interface USB to KNX RF
- Mounting kit included (without design frame)
- Connectors: USB Micro Type B, internal antenna
- Power supply via battery type CR2032
- Rockers for standard frames with internal dimensions 55 x 55 mm
- Dimensions wall mounting plate: 71 x 71 mm, for flush mounted box 68 mm

KNX RF / ENO Push Button 440 <i>secure</i> : Single rocker	Art. no. 5374	Gross price	93.00 €
KNX RF / ENO Push Button 440 <i>secure</i> : Double rocker	Art. no. 5326	Gross price	98.00 €

Frame Fusion 1-fold white – Frame for MATCH 55 series

Frame Fusion 1-fold anthracite – Frame for MATCH 55 series



Standard frame for MATCH 55 series (frame only).

- Budget solution for push button installations
- Available in two colors
- Dimensions (LxWxH): 85 x 85 x 11 mm

Frame 1-fold Fusion : white	Art. no. 5386	Gross price	3.80 €
Frame 1-fold Fusion : anthracite	Art. no. 5387	Gross price	6.60 €

Glass frame Fusion 1-fold white – Frame for MATCH 55 series

Glass frame Fusion 1-fold black – Frame for MATCH 55 series



Glass frame for MATCH 55 series (frame only).

- Design solution for push button installations
- Available in two colors
- Dimensions (LxWxH): 85 x 85 x 11 mm

Glass frame 1-fold Fusion : white	Art. no. 5388	Gross price	36.80 €
Glass frame 1-fold Fusion : black	Art. no. 5389	Gross price	38.00 €

KNX RF/TP Coupler 673 *secure* → see page 15

KNX ENO Gateways → see page 16

Note: Weinzierl offers single frames from the design series 'Fusion' in two colors and two materials including real glass. Fusion is a frame design of the brand Opus® by Jäger Direkt, Germany. For multiple frames or for alternative colors please contact Jäger Direkt / Jäger Fischer GmbH & Co. KG.

8 KNX RF

KNX RF USB Interface Stick 340 – KNX USB interface for RF



USB stick as interface to KNX RF. The device can be used as a programming interface for the ETS® software (ETS5 or higher).

- Support of KNX Long Frames
- Support of Weinzierl BAOS Protocol V2
- Connectors: USB Type A, internal antenna
- Dimensions (LxWxH): 71 x 23 x 8.7 mm

[KNX RF USB Interface Stick 340](#)

Art. no. 5110

Gross price

178.00 €

KNX RF/TP Coupler 673 *secure* – KNX media coupler for RF



KNX radio coupler in compact design (flush mounted housing). Support of KNX Security. The coupler connects KNX RF devices of a radio line with the KNX bus twisted pair. For KNX installations with ETS®.

- For the connection of KNX RF with KNX TP
- For KNX S-Mode (ETS)
- Support of KNX Data Security
- Support of KNX Long Frames
- Connections: KNX, internal antenna
- Compact flush mounted housing
- Dimensions (LxWxH): 48 x 40 x 18 mm

[KNX RF/TP Coupler 673 *secure*](#)

Art. no. 5188

Gross price

228.00 €

KNX RF / ENO Push Button 440 *secure* → see page 14

9 KNX EnOcean Gateways

KNX ENO 626 *secure* – KNX gateway to EnOcean 8-fold



Bidirectional, compact gateway between EnOcean and the KNX bus. The device supports encrypted radio communication with EnOcean Secure devices. Over 100 device profiles (EEP EnOcean Equipment Profiles) enable simple and secure connection of various EnOcean sensors and actuators to KNX installations.

- 8 channels for sensors, actuators or logic + 8 channels for logic only
- Integrated logic and control functions
- Support of EnOcean Security
- Support for over 100 profiles (EEP)
- Connections: KNX, internal antenna
- Compact flush mounted housing
- Dimensions (LxWxH): 48 x 40 x 18 mm

[KNX ENO 626 *secure*](#)

Art. no. 5269

Gross price

238.00 €

KNX ENO 636 *secure* – KNX gateway to EnOcean 32-fold



Bidirectional gateway between EnOcean and the KNX bus. The device supports encrypted radio communication with EnOcean Secure devices. More than 100 device profiles (EEP EnOcean EquipmentProfiles) allow an easy and secure connection of different EnOcean sensors and actuators to KNX installations.

- 32 channels for sensors, actuators or logic
- Integrated logic and control functions
- Support of EnOcean Security
- Support for over 100 profiles (EEP)
- Integrated graphic display
- Connections: KNX, internal antenna
- Housing for surface mounting, white
- Dimensions (LxWxH): 81 x 81 x 25 mm

[KNX ENO 636 *secure*](#)

Art. no. 5268

Gross price

408.00 €

KNX ENO 630/632/634 – KNX gateway to EnOcean (predecessor versions)



Uni-/Bidirectional gateway between EnOcean wireless devices and the KNX bus. Over 100 device profiles (EEP EnOcean Equipment Profiles) allow easy and secure connection of various EnOcean sensors and actuators to KNX installations.

Note: The devices are available until further notice.

*For new installations KNX ENO 626 *secure* and KNX ENO 636 *secure* are recommended.*

- 16/24/32 channels for sensors, actuators or logic
- Integrated logic and control functions
- Support for over 100 profiles (EEP)
- Integrated graphic display
- Connections: KNX, internal antenna
- Housing for surface mounting, white
- Dimensions (LxWxH): 81 x 81 x 25 mm

[KNX ENO 630](#): 16 channels, unidirectional

Art. no. 5129

Gross price

328.00 €

[KNX ENO 632](#): 24 channels, bidirectional

Art. no. 5136

Gross price

378.00 €

[KNX ENO 634](#): 32 channels, bidirectional

Art. no. 5137

Gross price

408.00 €

KNX RF / ENO Push Button 440 *secure* → see page 14



WEINZIERL ENGINEERING
GmbHAchatz 3-4
DE-84508 Burgkirchen an der Alz
Tel. : +49 8677 / 916 36 - 0
E-mail: info@weinzierl.de
Web: www.weinzierl.de

2021-01-28